

SKG-IKOB PRODUCTCERTIFICATE

637.653.01

Date of issue: 18-02-2025



Certificate holder

GIESSE S.p.A.

Via Tubertini 1

I-40054 Budrio (BO)

T: +39 51 8850677

E: infotechgiesse@schlegel.com

I: www.giesse.it



Declaration of SKG-IKOB

This certificate has been issued on the basis of BRL 3104 in accordance with the SKG-IKOB Regulations for Attestation, Certification and Inspection.

SKG-IKOB declares that the by or on behalf of the certificate owner produced building hardware product:

rim cam barrel hinge set of 3

delivered under logo / brand:

Giesse

delivered under type- and / or article number:

Domina HP 2 wings/3

meets class 3 STER according BRL 3104 and NEN 5089: 2009 if the product is indelibly marked with the SKG mark, as shown above.

For SKG-IKOB

A blue ink signature of ir. H.A.J. van Dartel, consisting of a stylized, cursive script.

ir. H.A.J. van Dartel
Certification manager

Verify at www.sterrenwijzer.nl if this certificate is still valid and actual.
This certificate contains 2 pages.

SKG-IKOB Certificatie
Poppenbouwing 56
4191 NZ Geldermalsen

Postbus 202
4190 CE Geldermalsen

T 088-2440100
info@skgikob.nl
www.skgikob.nl

CERTIFICATE

SKG-IKOB PRODUCTCERTIFICATE

GIESSE S.p.A.
Number: 637.653.01

page 2 of 2

1. PRODUCT

rim cam barrel hinge set of 3

PRODUCT TYPE

hinge

2. TECHNICAL SPECIFICATION

Operating:	N.A.
Construction:	1 barrel hinge of 2 parts: 1 frame- and 1 leafpart
System:	rim
Material:	frame and leaf part: aluminium coated OR anodised pen: hardened steel
Dimension:	frame-part: 51x38x36 mm leaf-part: 73x38x36 mm
Fixing:	direct mounting: 4x M12x55 mm through at least 2 walls of $\geq 1,5$ mm contra plate: 4x M8x55 mm
Intended use:	metal, door-inward-opening, door-outward-opening inside and outside opening aluminium doors and windows

3. DELIVERY

The preconditions for correct installation and the fasteners to be used are described in the enclosed or digitally published installation instructions with the following version:
I05370030QN/02-2025

4. PERFORMANCES

A rim cam barrel hinge set of 3 according this certificate fulfils the relevant requirements of BRL 3104.

A window- or door set, in which this rim cam barrel hinge, set of 3 is installed according the installation instructions of the certificate holder meets at least burglar resistance class (RC) 3 of NEN 5096 and EN 1627, if:

the façade element or the (profile-)system from which the element is manufactured is delivered under a (KOMO-)quality approval with respect to the aspect burglar resistance, in which the actual window or door type is admitted and the herein mentioned conditions are fulfilled.

A window or door, in existing buildings, in which this rim cam barrel hinge, set of 3 is installed according the installation instructions of the certificate holder, meets the requirements of the Police Mark Save Housing (PKVW) - Existing Building, if:

the other aspects of the façade element also comply with the applicable PKVW Protection directive (publication CCV).